



(updated 04/28/2023)			u	4
	Whisper Lift II PRO	Whisper Lift II	Whisper Lift XL	Whisper Lift XL
Lift Model		PRO Swivel	PRO	PRO Swivel
Lift SKU	23401	23501	23601	23602
Retracted Height	32 1/2"	32 1/2"	47 1/2"	47 1/2"
Extended Height	68 1/2"	68 1/2"	96 1/2"	96 1/2"
Depth	7"	9"	7"	9"
Stroke	36"	36"	49"	49"
Min TV Height	18"	18"	18"	18"
Max TV Height*	36"	36"	49"	49"
Max Weight - Upright (Combined TV, Components, Lid)	100lbs	75lbs	200lbs	75lbs
Max Weight - Dropdown	50lbs	50lbs	100lbs	75lbs
Max VESA Pattern Height	400mm	400mm	400mm	400mm
Max VESA Pattern Width	700mm	700mm	700mm	700mm
Flat-Top Lift Mount	Optional	Optional	Optional	Optional
Roller Top	Included	Included	Included	Included
Add-On Component Shelf	Optional	Optional	Optional	Optional
Wired Controller	✓	✓	✓	✓
Wireless Remote	RF and IR	RF and IR	RF and IR	RF and IR
IR Controls	✓	✓	✓	✓
Programmable Set Height Positions	1	1	1	1
12v Trigger Port	✓	✓	✓	✓
RS232 Port	X	X	X	X
WIFI Enabled	X	X	X	X

^{*} Max TV Height assumes no component shelf installed or components placed below TV. Max TV Height will decrease if component shelf is attached to lift or components are placed below the TV.

Whisper Lift II, Whisper Lift II PRO, and Whisper Lift XL PRO Features and Accessories

Roller Top (included)	Roller on top of lift that pushes lid open when lift is raised.	
Flat Top Lid Mount (optional – sku: 25092)	Flat steel plate that attaches to top of lift. Cabinet lid or ceiling material attaches to this plate and moves with the lift.	
Add-On Component Shelf (optional – sku: 25021)	Component shelf that attaches to lift and raises/lowers along with the TV. Components, like cable/satellite TV boxes, DVD players, can be placed on shelf for easy access.	
Wired Controller (included)	Controller that is connected to lift to control the lift.	
Wireless Controller (included)	Wireless remote control for controlling lift. Available in RF (radio-frequency) and IR. RF (Radio Frequency) – operates WITHOUT direct line of sight IR (Infra-Red) – operates WITH direct line of sight	
IR (Infra-Red) Controls (Whisper Lift II PRO and XL PRO only)	Receiver sensor provided with lift that plugs into lift control box and raises/lowers livia infra-red signal received from universal infra-red remote controls that can be particular.	
12v Trigger Port (Whisper Lift II PRO and XL PRO only)	3.5mm receiver port in control box that senses an input of 12volts provided by an outside source. Typically referred to as "contact closure". Constant 12v applied to port – lift raises Removal of 12v from port – lift lowers	

	SRV Series		SRV 360° Swivel Series	
Lift Comparison Chart (updated 04/28/2023)			3,605	■
Lift Model	SRV 2800	SRV 3900	SRV 2800 Swivel	SRV 3900 Swivel
Lift SKU	32800	33900	32820	33920
Retracted Height	27 1/16"	31 3/8"	27 5/8"	31 7/8"
Extended Height	55 1/16"	70 3/8"	55 5/8"	70 7/8"
Depth	4"	4"	4"	4"
Stroke	28"	39"	28"	39"
Min TV Height	18"	18"	18"	18"
Max TV Height*	28"	33 1/2"	28"	33 1/2"
Max Supported Weight	170lbs	170lbs	120lbs	120lbs
Max VESA Pattern Height	400mm	400mm	400mm	400mm
Max VESA Pattern Width	400mm	600mm	400mm	600mm
Flat-Top Lift Mount	Included	Included	Included	Included
Roller Top	Optional	Optional	Optional	Optional
Add-On Component Shelf	Optional	Optional	Optional	Optional
Wired Controller	✓	✓	✓	✓
Wireless Remote	RF and IR	RF and IR	RF and IR	RF and IR
IR Controls	✓	✓	✓	✓
Programmable Set Height Positions	2	2	2	2
RS232 Controls	✓	✓	✓	✓
12v Trigger Controls	X	X	X	X
WIFI Enabled		✓		✓

^{*} Max TV Height assumes no component shelf installed or components placed below TV. Max TV Height will decrease if component shelf is attached to lift or components are placed below the TV.

ValueLine and SRV Features and Accessories

Flat Top Lid Mount (included)	Flat steel plate that attaches to top of lift. Cabinet lid or ceiling material attaches to this plate and moves with the lift.
Roller Top (optional – sku: 30002)	Roller on top of lift that pushes lid open when lift is raised.
Add-On Component Shelf (optional – sku: 30011)	Component shelf that attaches to lift and raises/lowers along with the TV. Components, like cable/satellite TV boxes, DVD players, can be placed on shelf for easy access.
Wired Controller (included)	Controller that is connected to lift to control the lift.
Wireless Controller (included)	Wireless remote control for controlling lift. Available in RF (radio-frequency) and IR. RF (Radio Frequency) – operates WITHOUT direct line of sight IR (Infra-Red) – operates WITH direct line of sight
IR (Infra-Red) Controls (SRV Series Only)	Receiver sensor provided with lift that plugs into lift control box and raises/lowers lift via infra-red signal received from included IR remote.
RS232 Port	Serial communication port for controlling the lift RS232 serial communications commands.
Wifi Enabled Controls	Serial communication port for controlling the lift RS232 serial communications commands.